

HCVR-SQA SEQUENTIAL ACTIVATOR



STANDARD FEATURES

- UL Listed and FM Approved
- Capable of releasing two aerosol generators or canisters
- Includes a back box for surface mount
- LED indicates for output supervision trouble

DESCRIPTION

HCVR-SQA is a sequential activator that is used to operate fixed condensed aerosol generators or canisters for extinguishing fire in a confined space.

COMPATIBILITY LIST

CANISTER TYPE	GENERATOR TYPE
HOCHIKI AMERICA	
FNX-100S	FNX-1000
FNX-200S	FNX-2000
FNX-500S	FNX-3000
	FNX-5700
FIREPRO	
FP-100S	FP-1000
FP-200S	FP-2000
FP-500S	FP-3000
	FP-5700

SPECIFICATIONS

Models	HCVR-SQA
Supply Voltage	24VDC
Average Current Consumption	1mA
Maximum Output Current	1A @ 24VDC
Material	Mild Steel
Dimension	3.58" W x 3.58" H x 1.61" D

Specifications subject to change without notice.

Hochiki America Corporation

7051 Village Drive, Suite 100 Buena Park, CA 90621-2268

Phone: 714/522-2246 Fax: 714/522-2268

Technical Support: 800-845-6692 or technicalsupport@hochiki.com

Find latest revision at www.hochiki.com



F0167 04/2015

PRODUCT LISTINGS		
SIGNALING  LISTED S6468	 California State Fire Marshal 7300-0410:0207	 FM APPROVED 3046396

WIRING DIAGRAM

